



ALIN 4LED 1530mm NT

Lineárne svietidlo pre LED tuby T8




[V] 220-240 AC	[Hz] 50	[W] max 58	G13	IP 20	
[°C] 5÷25			[mm²] 1,5+2,5	L N ONE SIDE INPUT	
	CE	EAC			0,5m



ALIN 4LED 1X150-W-NT

		TYPE 			[mm]
ALIN 4LED 1X150-W-NT	27425	matné	biela	T8 LED	1540
ALIN 4LED 1X150-SR-NT	27427	matné	strieborná	T8 LED	1540
ALIN 4LED 1X150-B-NT	27426	matné	čierna	T8 LED	1540
AL 4LED 150-MPR-W-NT	28452	mikroprizmatický	biela	T8 LED	1540
AL 4LED 150-MPR-SR-NT	28454	mikroprizmatický	strieborná	T8 LED	1540
AL 4LED 150-MPR-B-NT	28453	mikroprizmatický	čierna	T8 LED	1540



- Materiál korpusu: hliníková zliatina
- Materiál difúzora: plast



ALIN 4LED 1X150-W-NT



ALIN 4LED 1X150-SR-NT



ALIN 4LED 1X150-B-NT



AL 4LED 150-MPR-W-NT

ALIN 4LED 1530mm NT


Lineárne svietidlo pre LED tuby T8




AL 4LED 150-MPR-SR-NT




AL 4LED 150-MPR-B-NT




ALIN 4LED 1X150-W-NT




ALIN 4LED 1X150-SR-NT




ALIN 4LED 1X150-B-NT



AL 4LED 150-MPR-W-NT



AL 4LED 150-MPR-SR-NT



AL 4LED 150-MPR-B-NT